


There is a change in the **LT1585A/LT1585A-3.3** data sheet. The minimum output capacitance required for stability is 100 $\mu$ F. The value of 100 $\mu$ F tantalum or aluminum output capacitor covers all applications, including those using a bypass capacitor on the adjust terminal.

This change does not affect any of the data sheet minimum/maximum specification limits. See below for the areas in the data sheet that are affected by this change which are indicated by **bold** type. For complete specifications, typical performance curves and applications information, please see the **LT1585A/LT1585A-3.3** data sheet.

## ELECTRICAL CHARACTERISTICS

PARAMETER		CONDITIONS	MIN	TYP	MAX	UNITS
Ripple Rejection	LT1585A	$f = 120\text{Hz}$ , $C_{OUT} = 100\mu\text{F}$ Tant., $(V_{IN} - V_{OUT}) = 3\text{V}$ , $I_{OUT} = 5\text{A}$				
	LT1585A-3.3	$f = 120\text{Hz}$ , $C_{OUT} = 100\mu\text{F}$ Tant., $V_{IN} = 6.3\text{V}$ , $I_{OUT} = 5\text{A}$	● 60	72		dB

## TYPICAL APPLICATION



\* REQUIRED FOR STABILITY

1585A TA01

## APPLICATIONS INFORMATION

### Stability

... For all operating conditions, the addition of a **100 $\mu$ F** solid tantalum or aluminum electrolytic on the output ensures stability. Many different types of ...

... The value of **100 $\mu$ F** tantalum or aluminum covers all cases of bypassing the adjust terminal. Normally, capacitor values on the order of ...

LT, LTC and LT are registered trademarks of Linear Technology Corporation.

For further information regarding this specification notice contact:

Linear Technology Corporation  
 1630 McCarthy Blvd.  
 Milpitas, California 95035-7417  
 Attn: Product Marketing Manager  
 Phone: (408) 432-1900