

·Micropower, Low Charge Injection, Quad CMOS Analog Switches with Data Latches

FEATURES

- Micropower Operation
- Single 5V or $\pm 15\text{V}$ Supply Operation
- Low Charge Injection
- Low R_{ON}
- Low Leakage
- Guaranteed Break Before Make
- Latch Resistant Design
- TTL/CMOS Compatible
- Improved Second Source for DG221/DG222
- Microprocessor Bus Compatible

KEY SPECIFICATIONS

- Supply Current $I^+ = 40\mu A, I^- = 5\mu A$ Max
- Charge Injection ($\pm 15V$ Supplies) $\pm 25pC$ Max
(Single 5V Supply) 2pC Typ
- R_{ON} 65 Ω Typ
- Signal Range $\pm 15V$


DESCRIPTION

The LTC221 and LTC222 are micropower, quad CMOS analog switches which typically dissipate only 250 μ W from ± 15 V supplies and 40 μ W from a single 5V supply. Onboard latches allow the LTC221 and LTC222 to interface directly to most microprocessor buses. The switches have 65 Ω typical on resistance and a very high off resistance. A break before make characteristic is inherent in these switches to prevent the shorting of two channels. The signal range is ± 15 V with a supply voltage of ± 15 V and 0V-5V with a single 5V supply. The switches have special charge compensation circuitry which greatly reduces charge injection to a maximum of ± 25 pC (± 15 V supplies).

The LTC221 and LTC222 are designed for applications such as microprocessor controlled programmable gain amplifiers, automatic test equipment, communication systems, and data acquisition systems. The LTC221 is normally closed and the LTC222 is normally open as shown in the Logic Table.

TYPICAL APPLICATION

Two-Channel, 12-Bit, Self-Calibrating Data Acquisition System



LTC221/222 • TA01

LTC221/LTC222

ABSOLUTE MAXIMUM RATINGS

(Note 1)

Voltages Referenced to V^-

V^+ 44V

GND 25V

Digital Inputs, S, D (Note 2) -2V to ($V^+ + 2V$) or
20mA, Whichever Occurs First

Current

Any Input Except S or D 30mA

Continuous S or D 20mA

Peak S or D

(Pulsed at 1ms, 10% Duty Cycle Max) 70mA

ESD Susceptibility (Note 3) 4kV

Power Dissipation (Plastic) 500mW

Power Dissipation (Ceramic) 900mW

Operating Temperature Range

LTC221C/LTC222C 0°C to 70°C

LTC221M/LTC222M -55°C to 125°C

Storage Temperature Range -65°C to 150°C

Lead Temperature (Soldering, 10 sec.) 300°C

PACKAGE/ORDER INFORMATION

TOP VIEW		ORDER PART NUMBER
		LTC221MJ LTC221CJ LTC221CN LTC221CS LTC222MJ LTC222CJ LTC222CN LTC222CS
J PACKAGE 16-LEAD CERAMIC DIP	N PACKAGE 16-LEAD PLASTIC DIP	
SO PACKAGE 16-LEAD PLASTIC SOIC		

LOGIC TABLE

IN_x	WR	LTC221	LTC222
0	0	On	Off
1	0	Off	On
X	1	Maintain Previous State	Maintain Previous State

DIGITAL AND DC ELECTRICAL CHARACTERISTICS

$V^+ = +15V$, $V^- = -15V$, GND = 0V unless otherwise noted.

PARAMETER	CONDITIONS			LTC221M/LTC222M			LTC221C/LTC222C			UNITS	
				MIN	TYP	MAX	MIN	TYP	MAX		
Analog Signal Range				●	± 15			± 15			V
R _{ON}	V _S = ± 10V I _D = 1mA	T _{MIN}			90			90			Ω
		25°C			65	90	65	90			
		T _{MAX}			135			135			
Off Input Leakage I _S (OFF)	V _D = ± 14V, V _S = ∓ 14V				0.01 ± 1			0.01 ± 5			nA
●				± 100			± 100				
Off Output Leakage I _D (OFF)	V _{IN} = 2.4V, LTC221 V _{IN} = 0.8V, LTC222				0.01 ± 1			0.01 ± 5			nA
				●	± 100			± 100			
On Channel Leakage I _D (ON)	V _D = V _S = ± 14V, V _{IN} = 2.4V, LTC222 V _{IN} = 0.8V, LTC221				0.02 ± 1			0.02 ± 5			nA
				●	± 200			± 200			
Input High Voltage V _{INH} , V _{WRH}				●	2.4			2.4			V
Input Low Voltage V _{INL} , V _{WRL}				●	0.8			0.8			V
Input High or Low Current I _{INH} , I _{INL} , I _{WRH} , I _{WRL}	V _{IN} = 15V, 0V V _{WR} = 15V, 0V			●	± 1			± 1			μA
C _S (OFF)					5			5			pF
C _D (OFF)					12			12			pF
C _D , C _S (ON)					30			30			pF
I ⁺	All Channels On or Off V _{IN} = V _{WR} = 0V or 4.0V				16 40			16 40			μA
I ⁻				●	60			60			
					0.1 5			0.1 5			
				●	10			10			

AC ELECTRICAL CHARACTERISTICS

$V^+ = +15V$, $V^- = -15V$, $GND = 0V$ unless otherwise noted.

PARAMETER	CONDITIONS	LTC221M/LTC222M			LTC221C/LTC222C			UNITS
		MIN	TYP	MAX	MIN	TYP	MAX	
T_{ON}	$V_S = 2V$, $R_L = 1k\Omega$, $C_L = 35pF$		290	400		290	400	ns
T_{OFF}			210	300		210	300	
T_{OPEN}		20	85		20	85		ns
Off Isolation	$V_S = 2Vp-p$, $R_L = 1k\Omega$ $f = 100kHz$		75			75		dB
Crosstalk			90			90		
Charge Injection Q_{INJ}	$R_{GEN} = 0\Omega$, $C_L = 1000pF$, $V_{GEN} = 0$		5	± 25		8	± 25	pC
Total Harmonic Distortion THD	$V_S = 2Vp-p$, $R_L = 10k\Omega$		0.01			0.01		%
T_{ON} , \overline{WR}	$V_S = 2V$, $R_L = 1k\Omega$, $C_L = 35pF$		270	400		270	400	ns
T_{OFF} , \overline{WR}			160	300		160	300	

DIGITAL AND DC ELECTRICAL CHARACTERISTICS

$V^+ = +5V$, $V^- = GND = 0V$ unless otherwise noted.

PARAMETER	CONDITIONS			LTC221M/LTC222M			LTC221C/LTC222C			UNITS
				MIN	TYP	MAX	MIN	TYP	MAX	
Analog Signal Range			●	0		5	0		5	V
R _{ON}	V _S = +1.5V, +3V I _D = 0.25mA	T _{MIN}				450			520	Ω
		25°C			280	450	280	520		
		T _{MAX}				650		650		
Off Input Leakage I _S (OFF)	V _D = 4V, 1V; V _S = 1V, 4V (Note 4)				0.01	±1		0.01	±5	nA
●					±100		±100			
Off Output Leakage I _D (OFF)					0.01	±1		0.01	±5	
			●			±100		±100		
On Channel Leakage I _D (ON)	V _D = V _S = 1V, 4V (Note 4)				0.01	±1		0.01	±5	nA
●					±200		±200			
Input High Voltage V _{INH} , V _{WRH}			●	2.4			2.4			V
Input Low Voltage V _{INL} , V _{WRL}			●			0.8			0.8	V
Input High or Low Current I _{INH} , I _{INL} , I _{WRH} , I _{WRL}	V _{IN} = 5V, 0V V _{WR} = 5V, 0V		●			±1			±1	μA
C _S (OFF)					5			5		pF
C _D (OFF)					12			12		pF
C _D , C _S (ON)					30			30		pF
I ⁺	All Channels On or Off				8	20		8	20	μA
	V _{IN} = V _{WR} = 0V or 4.0V		●			30			30	

AC ELECTRICAL CHARACTERISTICS $V^+ = +5V$, $V^- = GND = 0V$ unless otherwise noted.

PARAMETER	CONDITIONS	LTC221M/LTC222M			LTC221C/LTC222C			UNITS
		MIN	TYP	MAX	MIN	TYP	MAX	
T_{ON}	$V_S = 2V$, $R_L = 1k\Omega$, $C_L = 35pF$	450	600		450	600		ns
T_{OFF}		190	300		190	300		
T_{OPEN}		100	250		100	250		ns
Off Isolation	$V_S = 2V_{p-p}$, $R_L = 1k\Omega$ $f = 100kHz$	75			75			dB
Crosstalk		90			90			
Charge Injection Q_{INJ}	$R_{GEN} = 0\Omega$, $C_L = 1000pF$, $V_{GEN} = 2.5V$	2			2			pC
Total Harmonic Distortion THD	$V_S = 2V_{p-p}$, $R_L = 10k\Omega$	0.01			0.01			%
$T_{ON, WR}$	$V_S = 2V$, $R_L = 1k\Omega$, $C_L = 35pF$	430	600		430	600		ns
$T_{OFF, WR}$		160	300		160	300		

The ● denotes the specifications which apply over full operating temperature range. All other limits and typicals $T_A = 25^\circ C$.


Note 1: Absolute Maximum Ratings are those values beyond which the life of a device may be impaired.

Note 2: Signals on S, D, or IN exceeding V^+ or V^- will be clamped by internal diodes. Limit forward diode current to maximum current rating.


Note 3: In-circuit ESD on the switch pins (S or D) exceeds 4kV (see test circuit).

Note 4: Leakage current with a 5V supply is guaranteed by correlation with the $\pm 15V$ leakage current.


TYPICAL PERFORMANCE CHARACTERISTICS




LTC221/222 - TPC01




LTC221/222 - TPC02



LTC221/222 - TPC03



LTC221/222 - TPC04



LTC221/222 - TPC05



APPLICATIONS INFORMATION

Switching Time Test Circuit



Switch output waveform shown for V_S = constant with logic input waveform as shown. Note that V_S may be (+) or (–) as per switching time test circuit. V_O is the steady

state output switch on. Feedthrough via gate capacitance may result in spikes at leading and trailing edge of output waveform.

Switching Time Test Circuit




Charge Injection Test Circuit




ΔV_O IS THE MEASURED VOLTAGE ERROR DUE TO CHARGE INJECTION. THE ERROR VOLTAGE IN COULOMBS IS $\Delta Q = C_L \times \Delta V_O$.

OIRR-Off Isolation Test Circuit




CCRR-Channel to Channel Crosstalk Test Circuit



APPLICATIONS INFORMATION

Auto Ranging an 8-Channel, 10-Bit A/D Converter



8-Channel, 14-Bit A/D Converter

