

September 1998

The **LTC[®]1040** data sheet has been modified as shown in **bold** in the following table. For complete specifications, typical performance characteristics and applications information, please see the **LTC1040** data sheet.

 LTC and LT are registered trademarks of Linear Technology Corporation.

ELECTRICAL CHARACTERISTICS

Test conditions: $V^+ = 5V$, $V^- = -5V$, $T_{MIN} \leq T_A \leq T_{MAX}$ unless otherwise noted.

SYMBOL	PARAMETER	CONDITIONS		LTC1040M/LTC1040C			UNITS
				MIN	TYP	MAX	
V_{OS}	Offset Voltage (Note 1)	Split Supplies $\pm 2.8V$ to $\pm 6V$ Single Supply ($V^- = GND$) 2.8V to 6V	●		± 0.3	$\pm \mathbf{0.75}$	mV
		Split Supplies $\pm 6V$ to $\pm 8V$ Single Supply ($V^- = GND$) 6V to 15V	●		± 1	$\pm \mathbf{4.5}$	mV

Note 1: Applies over input voltage range limit and includes gain uncertainty.

For further information regarding this specification notice contact:

Linear Technology Corporation
 1630 McCarthy Blvd.
 Milpitas, California 95035-7417
 Attn: Product Marketing Manager
 Phone: (408) 432-1900