


April 1996

The **LTC[®]1064-1** data sheet has been modified from Rev 0 to Rev A. The changes are shown below and are indicated in **bold** type. For complete specifications, typical performance curves and applications information, please see the **LTC1064-1** data sheet.

 LTC and LT are registered trademarks of Linear Technology Corporation.

ELECTRICAL CHARACTERISTICS

$V_S = \pm 7.5V$, $f_{CLK} = 1MHz$, $R_L = 10k$, $C_L = 10pF$, $T_A = 25^\circ C$, TTL or CMOS clock input level, unless otherwise specified.

PARAMETER	CONDITIONS		MIN	TYP	MAX	UNITS
Output Voltage Swing and Operating Input Voltage Range	$V_S = \pm 2.37V$	●	± 1		1	V
	$V_S = \pm 5V$	●	± 3		3.2	V
	$V_S = \pm 7.5V$	●	± 5		5.2	V
Power Supply Current	$V_S = \pm 2.37V$	●		10	22	mA
	$V_S = \pm 5V$	●		12	23	mA
					26	mA
	$V_S = \pm 7.5V$, $f_{CLK} = 1MHz$	●		16	28 32	mA mA

For further information regarding this specification notice contact:

Linear Technology Corporation
 1630 McCarthy Blvd.
 Milpitas, California 95035-7417
 Attn: Product Marketing Manager
 Phone: (408) 432-1900, Ext. 2456