


February 1998

The specifications have been modified on the **LT[®]1302/LT1302-5** data sheet as indicated in **bold**. All other specifications remain unchanged. For complete specifications, typical performance curves and applications information, please see the **LT1302/LT1302-5** data sheet.

 LTC and LT are registered trademarks of Linear Technology Corporation.

ELECTRICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$, $V_{IN} = 2.5\text{V}$ unless otherwise noted.

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
Switch Current Limit	$V_C = \mathbf{0.1V}$ (Burst Mode [™] Operation)	0.6	1		A
	$V_C = 1.25\text{V}$ (Full Power) (Note 3)	2.0	2.8	3.9	A
Error Amplifier Voltage Gain	$0.9\text{V} \leq V_C \leq 1.2\text{V}$, $\Delta V_C / \Delta V_{FB}$	40	60		V/V

The ● denotes specifications which apply over the full operating temperature range.

Burst Mode is a trademark of Linear Technology Corporation.

Note 3: Minimum switch current 100% tested. Maximum switch current guaranteed by design.

For further information regarding this specification notice contact:

Linear Technology Corporation
1630 McCarthy Blvd.
Milpitas, California 95035-7417
Attn: Product Marketing Manager
Phone: (408) 432-1900