


The specifications for the **LTC[®]1345** have been revised as shown in **bold type** in the following table. For complete specifications, typical performance characteristics and applications information, please see the **LTC1345** data sheet.

 LTC and LT are registered trademarks of Linear Technology Corporation.

DC ELECTRICAL CHARACTERISTICS $V_{CC} = 5V \pm 5\%$ (Notes 2, 3), unless otherwise specified.

| SYMBOL | PARAMETER | CONDITIONS | MIN | TYP | MAX | UNITS |
|----------|-----------------------------|--|-----|-----|------------|---------|
| V_{OL} | Receiver Output Low Voltage | $I_O = 4mA$, $V_{A, B} = -0.2V$ | ● | | 0.4 | V |
| I_{CC} | V_{CC} Supply Current | Figure 1, $V_{OS} = 0V$, $S1 = S2 = HIGH$ | ● | 118 | 170 | mA |
| | | No Load, $S1 = S2 = HIGH$ | ● | 19 | 30 | mA |
| | | Shutdown, $S1 = S2 = 0V$ | ● | 1 | 100 | μA |

The ● denotes specifications that apply over the full operating temperature range.

Note 2: All currents into device pins are termed positive, all currents out of device pins are termed negative. All voltages are referenced to device ground unless otherwise specified.

Note 3: All typicals are given for $V_{CC} = 5V$, $C1 = C2 = C3 = 1\mu F$ ceramic capacitors and $T_A = 25^\circ C$.

For further information regarding this specification notice contact:

Linear Technology Corporation
 1630 McCarthy Blvd.
 Milpitas, California 95035-7417
 Attn: Product Marketing Manager
 Phone: (408) 432-1900