


August 1998

The **LT[®]1780/LT1781** data sheet has been modified to include the operating temperature range of -40°C to 85°C . The electrical characteristics are the same as the commercial temperature versions. The order numbers are shown below in **bold**. For complete specifications, typical performance curves and applications information, please see the **LT1780/LT1781** data sheet.

 LTC and LT are registered trademarks of Linear Technology Corporation.



ABSOLUTE MAXIMUM RATINGS

Operating Temperature Range

Commercial 0°C to 70°C

Industrial **-40°C to 85°C**

PACKAGE/ORDER INFORMATION

<div> <p>TOP VIEW</p>  <p> NC [1] 18 ON/OFF C1⁺ [2] 17 V_{CC} V⁺ [3] 16 GND C1⁻ [4] 15 TR1 OUT C2⁺ [5] 14 REC1 IN C2⁻ [6] 13 REC1 OUT V⁻ [7] 12 TR1 IN TR2 OUT [8] 11 TR2 IN REC2 IN [9] 10 REC2 OUT </p> <p> N PACKAGE 18-LEAD PDIP SW PACKAGE 18-LEAD PLASTIC SO </p> </div>	<div> <p>ORDER PART NUMBER</p> <p>LT1780CN LT1780CSW LT17801IN LT1780ISW</p> </div>	<div> <p>TOP VIEW</p>  <p> C1⁺ [1] 16 V_{CC} V⁺ [2] 15 GND C1⁻ [3] 14 TR1 OUT C2⁺ [4] 13 REC1 IN C2⁻ [5] 12 REC1 OUT V⁻ [6] 11 TR1 IN TR2 OUT [7] 10 TR2 IN REC2 IN [8] 9 REC2 OUT </p> <p> N PACKAGE 16-LEAD PDIP S PACKAGE 16-LEAD PLASTIC SO SW PACKAGE 16-LEAD PLASTIC SO </p> </div>	<div> <p>ORDER PART NUMBER</p> <p>LT1781CN LT1781CS LT1781CSW LT1781IN LT1781IS LT1781ISW</p> </div>
--	---	--	---

For further information regarding this specification notice contact:

Linear Technology Corporation
 1630 McCarthy Blvd.
 Milpitas, California 95035-7417
 Attn: Product Marketing Manager
 Phone: (408) 432-1900