

SN54ALS811, SN54AS811, SN74ALS811, SN74AS811 QUADRUPLE 2-INPUT EXCLUSIVE-NOR GATES WITH OPEN-COLLECTOR OUTPUTS

SDAS161 – D2837, MARCH 1984–REVISED OCTOBER 1988

- Package Options Include Plastic Small Outline Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability


description

These devices contain four independent Exclusive-NOR gates with open-collector outputs. They perform the Boolean functions $Y = A \oplus B = (A+B) \cdot (\bar{A}+\bar{B})$ in positive logic.

A common application is a true/complement element. If one of the inputs is high, the other input will be reproduced in true form at the output. If one of the inputs is low, the signal on the other input will be reproduced inverted at the output.

The SN54ALS811 and SN54AS811 are characterized for operation over the full military temperature range of -55°C to 125°C . The SN74ALS811 and SN74AS811 are characterized for operation from 0°C to 70°C .


logic symbol†




† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

Pin numbers shown are for D, J, and N packages.

SN54ALS811, SN54AS811 . . . J PACKAGE SN74ALS811, SN74AS811 . . . D OR N PACKAGE (TOP VIEW)



SN54ALS811, SN54AS811 . . . FK PACKAGE (TOP VIEW)



NC—No internal connection

FUNCTION TABLE (each gate)

INPUTS		OUTPUT
A	B	Y
L	L	H
L	H	L
H	L	L
H	H	H


SN54ALS811, SN54AS811, SN74ALS811, SN74AS811 QUADRUPLE 2-INPUT EXCLUSIVE-NOR GATES WITH OPEN-COLLECTOR OUTPUTS

SDAS161 – D2837, MARCH 1984–REVISED OCTOBER 1988

exclusive-NOR logic


An Exclusive-NOR gate has many applications, some of which can be represented better by alternative logic symbols.

EXCLUSIVE-NOR




These are five equivalent Exclusive-NOR symbols valid for an 'ALS811 gate in positive logic; negation may be shown at any one port or at all three of them.

LOGIC IDENTITY ELEMENT




The output is active (high) if all inputs stand at the same logic level (i.e., $A = B$).

EVEN-PARITY



The output is active (high) if an even number of inputs (i.e., only 0 or 2) are active.

ODD-PARITY ELEMENT



The output is active (low) if an odd number of inputs (i.e., only 1 of the 2) are active.

SN54ALS811, SN74ALS811
QUADRUPLE 2-INPUT EXCLUSIVE-NOR GATES
WITH OPEN-COLLECTOR OUTPUTS
SDAS161 – D2837, MARCH 1984–REVISED OCTOBER 1988

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC}	7 V
Input voltage	7 V
Off-state output voltage	7 V
Operating free-air temperature range: SN54ALS811	–55°C to 125°C
SN74ALS811	0°C to 70°C
Storage temperature range	–65°C to 150°C

recommended operating conditions

		SN54ALS811			SN74ALS811			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V_{IH}	High-level input voltage	2			2			V
V_{IL}	Low-level input voltage			0.7			0.8	V
I_{OH}	High-level output current			5.5			5.5	V
I_{OL}	Low-level output current			4			8	mA
T_A	Operating free-air temperature	–55		125	0		70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS		SN54ALS811		SN74ALS811		UNIT		
			MIN	TYP†	MAX	MIN		TYP†	MAX
V _{IK}	V _{CC} = 4.5 V,	I _I = −18 mA			−1.5		−1.5	V	
I _{OH}	V _{CC} = 4.5 V,	V _{OH} = 5.5 V			0.1		0.1	mA	
V _{OL}	V _{CC} = 4.5 V,	I _{OL} = 4 mA		0.25	0.4		0.25	V	
	V _{CC} = 4.5 V,	I _{OL} = 8 mA					0.35		
I _I	V _{CC} = 5.5 V,	V _I = 7 V			0.1		0.1	mA	
I _{IH}	V _{CC} = 5.5 V,	V _I = 2.7 V			20		20	μA	
I _{IL}	V _{CC} = 5.5 V,	V _I = 0.4 V			−0.1		−0.1	mA	
I _{CC}	V _{CC} = 5.5 V,	A at 4.5 V, B at 0 V		5	7.5		5	7.5	mA

† All typical values are at $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$.

switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 2 kΩ, T _A = MIN to MAX‡				UNIT
			SN54ALS811		SN74ALS811		
			MIN	MAX	MIN	MAX	
t _{PLH}	A or B	Y	25	60	25	55	ns
t _{PHL}	(other input low)		5	30	5	28	
t _{PLH}	A or B	Y	20	55	20	50	ns
t _{PHL}	(other input high)		5	28	5	23	

‡ The conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

NOTE 1: Load circuit and voltage waveforms are shown in Section 1 of the *ALS/AS Logic Data Book, 1986*.

SN54AS811, SN74AS811

QUADRUPLE 2-INPUT EXCLUSIVE-NOR GATES

WITH OPEN-COLLECTOR OUTPUTS

SDAS161 – D2837, MARCH 1984–REVISED OCTOBER 1988

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC}	7 V
Input voltage	7 V
Off-state output voltage	7 V
Operating free-air temperature range: SN54AS811	–55°C to 125°C
SN74AS811	0°C to 70°C
Storage temperature range	–65°C to 150°C

recommended operating conditions

		SN54AS811			SN74AS811			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V_{IH}	High-level input voltage	2			2			V
V_{IL}	Low-level input voltage			0.8			0.8	V
V_{OH}	High-level output current			5.5			5.5	V
I_{OL}	Low-level output current			20			20	mA
T_A	Operating free-air temperature	–55		125	0		70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54AS811			SN74AS811			UNIT
		MIN	TYP†	MAX	MIN	TYP†	MAX	
V_{IK}	$V_{CC} = 4.5$ V, $I_I = -18$ mA			–1.5			–1.5	V
I_{OH}	$V_{CC} = 4.5$ V, $V_{OH} = 5.5$ V			2			2	mA
V_{OL}	$V_{CC} = 4.5$ V, $I_{OL} = 20$ mA		0.35	0.5		0.25	0.5	V
I_I	$V_{CC} = 5.5$ V, $V_I = 7$ V			0.1			0.1	mA
I_{IH}	$V_{CC} = 5.5$ V, $V_I = 2.7$ V			20			20	μA
I_{IL}	$V_{CC} = 5.5$ V, $V_I = 0.4$ V			–0.5			–0.5	mA
I_{CCH}	$V_{CC} = 5.5$ V		19.5	28		19.5	28	mA
I_{CCL}	$V_{CC} = 5.5$ V		26	38		5	38	mA

† All typical values are at $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$.

switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 500 Ω, T _A = MIN to MAX‡				UNIT
			SN54AS811		SN74AS811		
			MIN	MAX	MIN	MAX	
t _{PLH}	A or B	Y	6.3	12.6	6.3	11.2	ns
t _{PHL}	(other input low)		2.8	7.5	2.8	6.4	
t _{PLH}	A or B	Y	5.9	12.8	5.9	11.5	ns
t _{PHL}	(other input high)		3.7	9.8	3.7	8.7	

‡ The conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

NOTE 1: Load circuit and voltage waveforms are shown in Section 1 of the ALS/AS Logic Data Book, 1986.

IMPORTANT NOTICE

Texas Instruments (TI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

TI warrants performance of its semiconductor products and related software to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

Certain applications using semiconductor products may involve potential risks of death, personal injury, or severe property or environmental damage ("Critical Applications").

TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS.

Inclusion of TI products in such applications is understood to be fully at the risk of the customer. Use of TI products in such applications requires the written approval of an appropriate TI officer. Questions concerning potential risk applications should be directed to TI through a local SC sales office.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards should be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor does TI warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.